



















## Technical specifications

Create Space 2 carpet tiles meet the requirements of EN 1307

Create Space 2		
Description	Tufted multi-pile height cut and loop pile carpet tile	
 Dimensions	50cm x 50cm	
 Total thickness	6.5mm ± 10%	
Pile height	3.0mm ± 0.5mm	
 Collection size	15 colourways 5m <sup>2</sup> per box	
 Application (Class 33) EN 1307	Class 33, Suitable for any type of heavy contract application	
Pile composition	100% ECONYL®/Altochroma polyamide 6*	
Dye method	100% solution dyed	
Stitch density	249,600 per m <sup>2</sup> ± 10%	
 Pile weight	570gsm ± 10%	
Total weight	3,865gsm ± 10%	
Primary backing	Polyester	
 Secondary backing	Modified bitumen & polyester fleece Also available in SOFTbac® secondary backing	
 Castor chair use EN 985	Minimum R Value: ≥ 2.4	
 Light fastness EN ISO 105-B02	≥ 5	
 Dimensional stability EN 986	< 0.2 %	
 Environmental	Materials used in the construction of Tessera carpet tiles are chosen for their low volatile organic compound (VOC) levels. Create Space carpet tiles are manufactured using 100% Green electricity. Create Space has up to 100% regenerated ECONYL® polyamide in each colourway.*	
 BRE	Create Space 2 is awaiting BREEAM assessment, please find the latest information at <a href="http://www.forbo-flooring.co.uk/createspace">www.forbo-flooring.co.uk/createspace</a>	
 CRI	Create Space 2 carpet tiles meet 01350 indoor air quality standard	
 CRUK	Forbo Flooring UK Ltd is a member of Carpet Recycling UK	
 Guarantee	Create Space 2 carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
 Installation method	Broadloom, quarter turn, tessellated, half drop or non-directional	

Create Space 2 carpet tiles meet the requirements of EN 14041

 Reaction to fire EN 13501-1	B <sub>fl</sub> -s1	
 Slip resistance EN 13893	DS: ≥0.30	
 Electrical resistance EN 10965 & EN1815	<1 x 10 <sup>9</sup> Ω: Static dissipative. Body voltage: Pass (< 2kV)	

\*For full details of the recycled yarn content per colourway please visit [forbo-flooring.co.uk/createspace](http://forbo-flooring.co.uk/createspace)