

# AZM Mandate 12 Specification Sheet



Product:	Mandate 12*
Reference picture:	
Fiber:	100% Polypropylene
Structure:	Loop pile: Multi-Level loop
Gauge:	1/12"
Stitches:	10 per inch
Tufts/sqm:	186000
Average Pile Height:	4.0+/-0.5mm
Total Height:	6.3+/-0.5mm
Pile Weight:	680g/sqm
Total Weight:	3370g/sqm ± 10%
Tile Size:	50*50cm
Backing:	E+Bac (Bitumen Backing)
Approved Installation Method:	<p>Monolithic      Quarter-turn      Brick</p>
Flammability:	ASTM E 645: $\geq 0.22$ watts/cm <sup>2</sup> Class II
Smoke Density:	ASTM E 662: $\leq 450$ DMC
Dimensional Stability	AACHEN: $\leq 0.2$ %
Tuft Bind:	ASTM D 1335: $\geq 8.0$ lbs
Delamination:	ASTM D 3936: $\geq 3.0$ lbc/in
Static Propensity	AATCC 134: $\leq 3.5$ kV
Colorfastness to Light	AATCC 16E: $\geq 4-5$
Colorfastness to Water	AATCC 107: $\geq 4-5$
Colorfastness to Crocking	AATCC 165: $\geq 4-5$



Office - Showroom: T: +90 212 274 44 22 | +90 212 274 42 89 E: info@anilzemin.com | bilgi@anilzemin.com Web: www.anilzemin.com

A: Vadi İstanbul Bulvarı 2A Apt, No:3/I , Kat:2 Daire: 15 - 16, Azerbaycan Cd., 34247 Ayazağa/Sarıyer/İstanbul

logistics 1: T: +90 212 229 44 38 | E: info@anilzemin.com | bilgi@anilzemin.com | www.anilzemin.com A: Poligon Mah. Sevim Sok. No:10/B İstinye / Sarıyer / İstanbul

logistics 2: Hellmann Worldwide Logistics