

Technical specifications

Enduro meets the requirements of EN ISO 10582



		Enduro Dryback	Enduro Click	
	Total thickness	EN-ISO 24346	2.0 mm	4.0 mm
	Wearlayer thickness	EN-ISO 24340	0.30 mm	0.30 mm
	Collection size		20	20
	Domestic use	EN-ISO 10874	23	23
	Commercial use	EN-ISO 10874	31	31
	Tile size	EN-ISO 24342	30.4 x 60.9 cm	30.5 x 61 cm
	Plank size	EN-ISO 24342	17.7 x 121.9 cm	18.5 x 121.2 cm
	Packaging per carton tiles		4.09 m ² (22 pcs)	2.23 m ² (12 pcs)
	Packaging per carton planks		4.77 m ² (22 pcs)	2.24 m ² (10 pcs)
	Squareness and straightness	EN-ISO 24342	< 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
	Total weight	ISO 23997	ca. 3000 g/m ²	ca. 6700 g/m ²
	Wear layer Binder Content	EN-ISO 10582	Type 1	Type 1
	Slip resistance	DIN 51130	R10	R10
	Acoustical impact noise reduction	EN-ISO 717-2	5 dB	6 dB / 15 dB in combination with Forbo underlay
	Castor chair continuous use	ISO 4918	Good	Good
	Residual indentation	ISO 24343-1	≤ 0.10 mm	≤ 0.10 mm
	Light fastness	ISO 105-B02	≥ 6	≥ 6
	VOC emissions reaction to fire	EN-IS 160009	≤ 100 µg/m ³	≤ 100 µg/m ³
	Resistance to chemicals	ISO 26987	Good	Good
	Dimension stability	EN-ISO 23999	≤ 0.10%	≤ 0.10%
	Fire resistance	EN 13501	B _f -s1, G, NCS	B _f -s1, L, NCS with and without Forbo underlay
	Slip resistance	EN 13893	DS - µ > 0.30	DS - µ > 0.30
	Thermal conductivity	ISO 8302	0.25 W/mK	0.25 W/mK
	Body voltage	EN 1815	< 2 kV	< 2 kV