

Technical specifications

Sphera StarT meets the requirements of EN ISO 10581		•
Binder content	EN ISO 10581	type 1
Total thickness	EN ISO 24346	2.0 mm
Surface finish		Reinforced PUR coating
Collection size		30
Commercial use	EN ISO 10874	34 very heavy
Light industrial use	EN ISO 10874	43 heavy
Roll width	EN ISO 24341	2 m
Roll length	EN ISO 24341	± 20 m
Total weight	EN ISO 23997	2.8 kg/m ²
Dimensional stability	EN ISO 23999	≤ 0.25 %
Residual indentation	EN ISO 24343-1	~ 0.02 mm
Abrasion resistance	EN 660-2	group T
Castor chair continuous use	ISO 4918 / EN 425	pass
Light fastness	ISO 105-B02	≥ 6
Flexibility	EN ISO 24344	0 7 mm
Seam strength	EN 684	270N/50mm
Resistance to chemicals	EN ISO 26987	very good
Slip resistance	DIN 51130	R9
Bacteria resistance	EN 846	does not support growth
Indoor Air Emissions: TVOC after 28 days	ISO 16000-6	A+
Sphera StarT meets the requirements of EN 14041		02003
Reaction to fire	EN 13501-1	B _{ff} -s1, G, CS
Slip resistance	EN 13893	μ ≥ 0.30
Body voltage	EN 1815	≤ 2 kV
Thermal conductivity	EN 12524	0.25 W/m-K





Homogeneous Vinyl

sphera[®] starT





Vadi İstanbul Bulvar 2A Apt, No:3/I , Kat:2 Daire: 15 - 16, Azerbaycan Cd., 34247 Sarıyer/İstanbul T: +90 212 274 44 22 | +90 212 274 42 89 E: info@anilzemin.com | bilgi@anilzemin.com Web: www.anilzemin.com



A game changer for effective solutions

Sphera StarT homogeneous floor coverings add style to demanding areas with their modern color palette and non-directional pattern. Whether it is a hospital, a school or a public area, the collection offers an effective flooring solution thanks to its high PVC content, excellent durability and unique performance.

Sphera StarT's reinforced PUR coated surface treatment resists dirt and scratches, is easy to clean and maintain, ensuring hygienic floors. The collection is %100 phthalate free and helps you to create a healthy indoor environment with low VOC emissions.

6732 white grey



