



The rich tapestry of landscape that forms the unique Scottish island of Arran, has influenced artists for generations. The quality of light and the huge variety of natural colours create a complex palette that changes with each season. From the muted hues of autumn bracken to the vibrant tones of the summer heather, Arran has a beauty that inspires.

- A collection of 12 naturally inspired semi-plain colourways
- Rich, heavyweight texture for luxury underfoot comfort
- Easily combined with Allura Flex vinyl tiles using the same adhesive, without the need for transition strips, additional profiles, or inconvenient build-up of the sub floor
- Meets SKA rating for M12 soft floor coverings
- Contains 57% recycled content by weight
- 100% Invista Antron Lumena solution dyed polyamide 6.6 yarn for durability and colour fastness



57% recycled content by weight



textured loop construction for structure and pattern




50cm x 50cm carpet tile





Arran colour options





Arran installation ideas
























Arran fitting options







quarter turn

tessellated

Forbo Environmental Data Sheet

Product name	Tessera Arran
Product description	Tessera Arran is a multi height, textured loop pile carpet tile with an 'artisan' appearance that broadlooms well. Arran is manufactured with 100% solution dyed yarn for superior colour fastness. Arran complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000°



Our footprint - how it's made

Total recycled content of product by weight	57%	ISO 9001 Quality Management System	R		
	57%		ISO 9001		
		ISO 14001 Environmental Management System			
Post industrial recycled content	57%	ISO 45001 Occupational Health and Safety Management			
% renewable electricity & biogas used	100%	Arran is made in an SA8000® certified facility			
Carbon footprint					
Estimated carbon footprint using	Raw materials and production	18.0 kg CO ₂ eq/m ²			
data from Environmental product declaration according to ISO 14025	Use (1 year)	se (1 year) 0.804 kg CO ₂ eq/m ²			
Health and well being					
Air quality CHPS 01350 AgBB/DiBt	Tessera products comply to 01350 Indoor Air Quality Standard Pass				
Impact sound reduction	25 dB				
Installation					
Recommended adhesives	Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended.				
	Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond.				
	Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol 640 Eurostar special.				

Forbo Environmental Data Sheet - continued

Maintenance

Appropriate care and maintenance is essential to longevity and appearance retention and is necessary to maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring Systems.

All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non-hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.

End of life

Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle used carpet tiles in the UK.

Acoustic performance up to 1 point

Contribution to Green Building Schemes

BREEAM 2014

BREEAM ratings	Building Type Office B	Education B	Health A	Domestic B	Retail (Durability) B	Retail (Fashion) A+
BREEAM 2018						
	Compliant throu	igh declaration n	umber 47882944	59.119.1 Valid until .	January 2024	
LEED (version 4)						
Potential direct or indirect contribution to following categories and credits:	Materials and R	Resources				
			Building pro up to 1 poin		optimisation - sourc	ing of raw materials -
			Construction	n and demolition wa	ste management up	o to 2 points
	Indoor environ quality	mental	Low emittin	g materials up to 3 p	oints	

Forbo design principles (Reduce, Recycle, Reuse, Renew)

visit www.forbo-flooring.co.uk/downloads for more information

Reduce	Investment in an extruder has reduced our bitumen usage by 50%.	
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.	
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles contain at least 56% recycled content by weight.	
Renew	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).	

Technical specification

Tessera Arran carpet tiles meet the requirements of EN 1307

	Description	'	Tufted multi-height loop pile carpet tile
	Dimensions	EN 994	50cm x 50cm (Other sizes available for special orders)
÷	Total thickness	ISO 1765	7.0mm ± 10%
	Pile height	ISO 1766	4.0mm ± 0.5mm
	Collection size		12 colourways. 4m² per box
##	Commercial use	EN ISO 10874	Class 33, Suitable for any type of heavy contract application
	Pile composition		100% Invista Antron® Lumena polyamide 6.6
	Dye method		100% solution dyed
	Stitch density	ISO 1763	$202,960 \text{ per } m^2 \pm 10\%$
R	Pile weight	ISO 8543	950 gsm ± 10%
	Total weight	ISO 8543	$4,465 \text{ gsm} \pm 10\%$
	Primary backing		Polyester
	Secondary backing		ProBac recycled mineral filler with low amount of modified bitumen, and polyester fleece. Contains over 76% recycled content. Also available in SOFTbac® secondary backing.
	Castor chair use	ISO 4918	Minimum R Value: ≥ 2.4 Overall R value: 2.9
\$	Light fastness	EN ISO 105-B02	≥5
K N	Dimensional stability	EN 986	≤ 0.2%
	Impact sound reduction	ISO 10140-3	25 dB
	Creating Better Environments Renewable Energy Recycled Content		All Tessera tufted carpet tiles are manufactured using 100% renewable energy (electricity & biogas) Arran carpet tiles contain 57% recycled content by weight
14	Indoor Air Quality		Arran carpet tiles comply to 01350 Indoor Air Quality Standard
Forbs	Back to the Floor		Installation off cuts can be collected via Back to the Floor
	Ska Rating		Arran meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
	Prodis-GUT	www.pro-dis.info	2E322B85
	Installation method		Monolithic, quarter turn, brick or tessellated
	Arran carpet tiles meet the requi	rements of EN 14041	
	Product code	EN 14041	1170100-DoP-101
B ₁₋₄₁ NCS	Reaction to fire	EN 13501-1	B _{fi} -s1, L, NCS
7.5° 6.6°	Slip resistance	EN 13893	μ≥ 0.30
75 Å	Body voltage	ISO 6356	< 2.0 kV

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Tessera Arran is manufactured in a facility certified to SA8000® and ISO 45001.

Contact us



Forbo Flooring Systems is part of the Forbo Group, a global leader in flooring and movement systems, and offers a full range of flooring products for commercial and affordable housing and new build markets. High quality linoleum, vinyl, textile, flocked and entrance flooring products combine functionality, colour and design, offering total flooring solutions for any indoor environment.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this brochure are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this brochure and does not represent that the information is accurate, complete or current and you are advised to visit our website at **www.forbo-flooring.co.uk** for up-to-date details or corrections to such contents.

UK

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT Email: info.flooring.uk@forbo.com

London EC1 showroom

79 St John Street, Clerkenwell London EC1M 4NR Tel: 0207 553 9300 Email: ec1@forbo.com

For commercial enquiries:

If calling from the North, London & South East Tel: 0800 0282 162 bcs.flooring.uk@forbo.com

If calling from Scotland, Midlands & South West Tel: 0800 0935 258 kcs.flooring.uk@forbo.com

Nuway enquiries:

Tel: 01773 740 688 efs.flooring.uk@forbo.com

Residential enquiries:

Tel: 0800 0935 846 Email: krcs.flooring.uk@forbo.com www.forbo-flooring.co.uk

SAMPLE SERVICE 0800 731 2369 samples.uk@forbo.com

Samples can be ordered over the phone, by calling **0800 731 2369** (Mon-Fri, 8.30am-5.00pm)

Samples can be ordered 24/7 by visiting www.forbo-flooring.co.uk/samples or by emailing samples.uk@forbo.com

Ireland

Forbo Ireland Ltd 2 Deansgrange Business Park Blackrock Co Dublin

Tel: 00353 1 2898 898 Fax: 00353 1 2898 177 Email: info.ireland@forbo.com www.forbo-flooring.ie

Registered office:

Forbo Flooring UK Limited High Holborn Road Ripley Derbyshire DE5 3NT Registered in England 9200318

