


# AZM Transitions PA Specification Sheet



## Technical Specifications

Style Name	Transitions PA	Tile Size	25cm*100cm
Construction	Multi-level Loop	Anti-microbial	Ultra-Fresh (Available)
Fiber	Nylon 6	Installation Method	
Gauge	1/12"		
Stitches	11 per inch		
Pile Weight	18oz/yd <sup>2</sup> (610g/sqm)		
Average Pile Height	4.0mm±0.5 mm		
Backing	E+Bac		
Total Thickness	6.3mm±0.5 mm		



	Test Code	Standard	Test Results
<b>Flammability Tests</b>			
Radiant Panel	ASTM E 648	≥ 45 watt/cm	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
<b>Stability</b>			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
<b>Anti-Static</b>			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
<b>Colour Fastness</b>			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
<b>Wear Tests</b>			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
<b>Generic Tests</b>			
Green Carpet(VOC)	CRI Green Label	GLP 6331 <sup>#</sup> /6332 <sup>#</sup>	Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)



# Declare.



**LIVING BUILDING CHALLENGE**



**3R** Reduce Reuse Recycle = Infinity Green!



## ANIL ZEMİN MARKET

**Merkez Ofis - Showroom**

**Lojistik - Depo**

**Lojistik - Depo 2**

Vadi İstanbul Bulvar 2A Apt, No:3/1, Kat:2 Daire: 15-16,  
Azerbaycan Cad. Ayazağa Mah. Sarıyer/İstanbul

Poligon Mah. Sevim Sok. No:10/B İstinye / Sarıyer / İstanbul

Hellmann Worldwide Logistics -Beylikdüzü OSB Mah.  
Mermerciler Sanayi Sitesi, 7. Cd. No:5, Beylikdüzü/İstanbul

Tel: 0 212 274 44 22

Tel: 0 212 274 42 89

Tel: 0 212 274 42 90