

Forbo Environmental Data Sheet

Product name	Tessera Infused
Product description	A unique fusion of naturally inspired elements, Tessera Infused combines soft organic patterning with natural structures. Infused complies with all requirements of EN1307: Textile Floor Coverings – Classification of Pile Carpets.
Manufacturing location	Bamber Bridge, United Kingdom
Site accreditation	ISO14001, ISO 9001, ISO 45001, SA8000°

640 Eurostar special.



Our footprint - how it's made

Environmental data		Independent assessment and rating	
Total recycled content of product by weight	60%	ISO 9001 Quality Management System	
		ISO 14001 Environmental Management System	
Post industrial recycled content	60%	ISO 45001 Occupational Health and Safety Management	ational and Safety gement
% renewable electricity & biogas used	100%	Tessera is made in an SA8000° certified facility	
Carbon footprint			
Estimated carbon footprint using data from Environmental product declaration according to ISO 14025	Raw materials and production	Awaiting result of the EPD	
	Use (1 year)	Awaiting result of the EPD	
Your footsteps – how it Health and well being Indoor Air quality AqBB/DiBt	Gold Pass		
Impact sound reduction	26 dB		
Installation			
Recommended adhesives	Carpet tiles must be adhered using an all over tackifier adhesive system: Forbo Eurocol 542 Eurofix Tack Plus, a solvent free release system, is recommended. Where periphery tiles are not constrained by fixtures e.g. walls, edge strips etc, it is recommended that such tiles are adhered using a permanent adhesive; Forbo Eurocol 640 Eurostar Special, again a solvent free adhesive is recommended. Adhesives must be applied according to the manufacturer's instructions and it is essential that tackifier adhesives are allowed to dry to a tacky finish before laying the carpet tile. Failure to do so could result in a permanent non-release bond. Where contribution to credits for BREEAM sections HEA2 and HEA9 are required then low emission		

adhesive Eurocol 542 tack plus should be used. If a permanent bond is required, please use Eurocol



creating better environments

Maintenance			
		nance is essential to longevity and appearance retention and is necessary to	
	maintain product warranties. Refer to the clean and care instructions available from Forbo Flooring System All Tessera products are suitable for cleaning using the Dry Fusion technique. Dry Fusion uses 95% less water than the normal system of cleaning, produces no waste product, uses non hazardous and biodegradable cleaning solutions and all packaging and materials within the Dry Fusion System can be recycled.		
End of life			
	Products suitable for reuse, recycling, downcycling and waste to energy. Forbo Flooring Systems works with recycling companies to clean, reuse and recycle old carpet tiles in the UK.		
Contribution to Gree	n Building Schemes		
BREEAM 2018			
	Awaiting result of the EPD		
LEED (version 4)			
Potential direct or indirect contribution to following	Materials and Resources		
categories and credits:		Building product disclosure and optimisation - sourcing of raw materials - up to 1 point	
		Construction and demolition waste management up to 2 points	
	Indoor environmental quality	Low emitting materials up to 3 points	
		Acoustic performance up to 1 point	
Forbo design principles (Red	uce, Recycle, Reuse, Renew)		
Reduce	Investment in an extruder has reduced our bitumen usage by 50%.		
Reuse	Yarn ends are rewound and used in the production of new Tessera Carpet tiles. All Tessera samples can be returned allowing them to be reused or recycled, reducing the need for virgin materials.		
Recycle	Yarns, backing cloth, fillers and latex all contain recycled materials. All tufted Tessera carpet tiles made in the UK contain at least 57% recycled content by weight.		
Renew	All Tessera carpet tiles manufactured at Bamber Bridge are made with 100% renewable forms of energy (renewable electricity & biogas).		
visit www.forbo-flooring.co.u	ık/downloads for more informatic	on	