

MEDITATION

COLLECTION

SPECIFICATION
SHEET

VOXFLO^R
passion and purpose



Performance Specifications

	Test Code	Standard	Test Result
Flammability Tests			
Radiant Panel	ASTM E 648	≥.45 watt/cm ²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
Stability			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
Anti-Static			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
Colour Fastness			
Light	AATCC 16 E	≥ 4	4-5
Rubbing/Crocking	AATCC 165	≥ 4	4-5
Wear Tests			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 2.5	3
Acoustic Tests			
EcoAce-Bac@	EN ISO 354		αw = 0.30 (H)
EcoAce-Bac@	EN ISO 10140-1		ΔLw = 28 dB
EcoAce-Bac@ Pro	EN ISO 354		αw = 0.30 (H)
EcoAce-Bac@ Pro	EN ISO 10140-1		ΔLw = 29 dB

MINDFUL PATH

MEDITATION COLLECTION

Technical Specifications

Construction: Multi-level Loop

Fiber: PUREWEAVE™ Nylon

Gauge: 1/12"

Stitches: 13 per inch

Area per carton: 6m²

Traffic Classification: Commercial - Heavy Duty

Average Pile Height: 3.5 ± 0.5 mm

Standard Backing: EcoAce-Bac®

Tile Size: 25 x 100 cm


Pile Weight: 17 OZ/yd²

Total Thickness: 5.5 ± 0.5 mm

Piece per carton: 24 pieces

Anti-microbial: Ultra Fresh (Available)

Installation Methods



Ashlar

**These given methods of installation are considered as classic solutions.

However, certain cases and needs may be different, and designs will differ accordingly.

Certifications



ISO 9001:2015
ISO 14001:2015

DOWNLOAD



DOWNLOAD



*Carbon Footprint
Carbon Neutrality

DOWNLOAD



DOWNLOAD



DOWNLOAD

Declare.



DOWNLOAD



DOWNLOAD



DOWNLOAD



DOWNLOAD

Warranty

Lifetime Commercial Limited Warranty

DOWNLOAD

Additional Information

- VOXFLOOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.


Additional Files

Installation Guidelines

DOWNLOAD

Maintenance Guidelines

DOWNLOAD





Performance Specifications

	Test Code	Standard	Test Result
Flammability Tests			
Radiant Panel	ASTM E 648	≥45 watt/cm ²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
Stability			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
Anti-Static			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
Colour Fastness			
Light	AATCC 16 E	≥ 4	4-5
Rubbing/Crocking	AATCC 165	≥ 4	4-5
Wear Tests			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 2.5	3
Acoustic Tests			
EcoAce-Bac@	EN ISO 354		αw = 0.30 (H)
EcoAce-Bac@	EN ISO 10140-1		ΔLw = 28 dB
EcoAce-Bac@ Pro	EN ISO 354		αw = 0.30 (H)
EcoAce-Bac@ Pro	EN ISO 10140-1		ΔLw = 29 dB

ZEN GLOW

MEDITATION COLLECTION

Technical Specifications

Construction: Multi-level Loop

Fiber: PUREWEAVE™ Nylon

Gauge: 1/12"

Stitches: 13 per inch

Area per carton: 6m²

Traffic Classification: Commercial - Heavy Duty

Average Pile Height: 3.5 ± 0.5 mm

Standard Backing: EcoAce-Bac®

Tile Size: 25 x 100 cm


Pile Weight: 17 OZ/yd²

Total Thickness: 5.5 ± 0.5 mm

Piece per carton: 24 pieces

Anti-microbial: Ultra Fresh (Available)

Installation Methods



Ashlar

**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications



ISO 9001:2015
ISO 14001:2015

DOWNLOAD



DOWNLOAD



*Carbon Footprint
Carbon Neutrality

DOWNLOAD




DOWNLOAD



DOWNLOAD

Declare.

DOWNLOAD



DOWNLOAD



DOWNLOAD



DOWNLOAD



DOWNLOAD

Warranty

Lifetime Commercial Limited Warranty

DOWNLOAD

Additional Information

- VOXFLOOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.


Additional Files

Installation Guidelines

DOWNLOAD

Maintenance Guidelines

DOWNLOAD





VOXFLOR[®]

www.voxflor.com

Shanghai **Headquarters**

T +86 21 62989325

Milano Creative Studio

T +39 3885863150

China **Branch Offices**

Beijing/ Guangzhou/ Shenzhen/ Xiamen

