

Employ Loop

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Employ Loop			
Type	Tufted Level Loop Pile			
Yarn	100% Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	5.6 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4197001 Raffia	4197002 Truffle	4197003 Shadow	4197004 Caramel
	4197005 Praline	4197006 Shale	4197007 Nutmeg	4197008 Fountain
	4197009 Jet	4197010 Rye	4197011 Cirrus	4197012 Atlantic
	4197013 Crystal	4197014 Tropical	4197015 Kiwi	4197016 Nordic
	4197017 Peacock	4197018 Eden	4197019 Baring	4197020 Oxford
	4197021 Clementine	4197022 Sapphire	4197023 Lavender	4197024 Salsa
	4197025 Cotton	4197026 Ground	4197027 Urban	4197028 Ash
	4197029 Granite	4197030 Gritstone	4197031 Sands	4197032 Autumn
	4197033 Brick	4197034 Fern	4197035 Everglade	4197036 Ink
Method of laying	Monolithic & Quarter Turn Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465