

Natural History Collection

NH610
NH611

Interface®

Natural History Collection

Clean. Calm. Considered.

Natural beauty doesn't need to be loud. The Natural History collection takes its cue from the quiet impact of the natural world - clean lines, layered textures, and a simplicity that lets nature do the talking.

NH610 channels wide, open landscapes with soft washes and organic flow. NH611 brings structure and energy through intersecting lines and rhythmic detail.

Designed to perform. Made to last.

(COVER) **PRODUCT** NH610 **COLOUR** SLATE **INSTALLED** NON DIRECTIONAL
PRODUCT NH611 **COLOUR** SEABREEZE **INSTALLED** MONOLITHIC

PRODUCT NH610 **COLOUR** BASALT **INSTALLED** NON DIRECTIONAL
PRODUCT NH610 **COLOUR** SLATE **INSTALLED** NON DIRECTIONAL
PRODUCT NH611 **COLOUR** MARIGOLD **INSTALLED** MONOLITHIC



PRODUCT NH610 **COLOUR** OLIVE **INSTALLED** NON DIRECTIONAL



PRODUCT NH611 **COLOUR** ASH **INSTALLED** MONOLITHIC
PRODUCT NH610 **COLOUR** MARIGOLD **INSTALLED** NON DIRECTIONAL



PRODUCT NH610 **COLOUR** ASH **INSTALLED** NON DIRECTIONAL
PRODUCT NH610 **COLOUR** SLATE **INSTALLED** NON DIRECTIONAL
PRODUCT NH611 **COLOUR** CHARCOAL **INSTALLED** MONOLITHIC




PRODUCT NH610 **COLOUR** WHEAT **INSTALLED** NON DIRECTIONAL
PRODUCT NH610 **COLOUR** TERRACOTTA **INSTALLED** NON DIRECTIONAL

NH610 Colour Range



7941205000 ASH



7941206000 WHEAT



7941202000 SLATE



7941203000 BASALT


7941204000 CHARCOAL


7941210000 TERRACOTTA


7941208000 OLIVE


7941207000 MARIGOLD


7941209000 SEABREEZE


7941211000 COBALT

Specifications

Style Code	7941
Product Construction	Tufted Patterned Textured Loop
Yarn System	100% Solution Dyed Nylon
Machine Gauge	1/12th
Pile Thickness	2.5 mm (± 0.5 mm)
Total Thickness	6.0 mm (± 0.5 mm)
Tile Size	50 x 50 cm
Area of Use	Commercial Heavy Use
Lifetime Antimicrobial	Intersept®
Soil / Stain Protection	Protekt2®

Installation Methods



NON DIRECTIONAL


QUARTER TURN



PPRODUCT NH611 **COLOUR** COBALT **INSTALLED** MONOLITHIC


NH611 Colour Range




7942205000 ASH




7942206000 WHEAT



7942202000 SLATE



7942203000 BASALT




7942204000 CHARCOAL




7942210000 TERRACOTTA



7942208000 OLIVE



7942207000 MARIGOLD



7942209000 SEABREEZE



7942211000 COBALT

Specifications

Style Code	7942
Product Construction	Tufted Patterned Textured Loop
Yarn System	100% Solution Dyed Nylon
Machine Gauge	1/12th
Pile Thickness	2.5 mm (± 0.5 mm)
Total Thickness	6.0 mm (± 0.5 mm)
Tile Size	50 x 50 cm
Area of Use	Commercial Heavy Use
Lifetime Antimicrobial	Intersept®
Soil / Stain Protection	Protekt2®

Installation Methods



MONOLITHIC

Why Our Modular Flooring?

Modular Flooring
Performance and flexibility. Interface's standard backing systems set the industry standard for modular performance. Tiles stay on the floor with no upcurl, no tapping and no rippling effect, yet are easy to selectively replace. Our modular carpet is easier to handle than bulky roll carpet and produces an average of just 2-5% waste compared to roll carpet's average of 15% . And it installs seamlessly with our LVT, no transition strips needed.

ReEntry
At Interface, an *end of life solution* of our products is a reality. ReEntry is our innovative programme to reclaim materials used in our product. Taking back our product at end of life is a service we provide our customers to ensure that none of the products they use will end up in landfill. Whether it is recycling into new product or re-purposing, we see our customer's waste as an opportunity for new product life.

TacTiles®
No glue installation. Our revolutionary TacTiles installation system eliminates the need for glue, adhering tiles securely together to form a floor that "floats" for greater flexibility, easier replacement and long-term performance. The result? Less mess, less waste and virtually no VOCs, not to mention an environmental footprint that is over 90% lower than that of traditional glue adhesives.

Intersept®
Mold protection. Our proprietary preservative, Intersept, protects our modular carpet against mould growth and odour-causing bacteria—guaranteed. Intersept treated carpet, with proper maintenance, shows no mould or bacterial growth when tested as per the ASTM E2471 Standard Test Method. Intersept is EPA-approved for safe use in carpet, water insoluble and contains no halogens, heavy metals, phenols or formaldehyde.

Protekt²®
Stain protection. The life and performance of your flooring is extended with Protekt², our patented stain resistant protection. Protekt² uses advanced technology to provide a lasting barrier against permanent soiling and staining, which simplifies the cleaning process and enhances the longevity of your carpet. Protekt² is product specific, please refer to individual product specifications for details.

Health Product Declaration (HPD) –
A transparency tool for evaluating whether a product supports Green Chemistry. As part of our work on Health and Materials, Interface continuously reduces the environmental and health impacts of our products through elimination of materials of concern.

15-Year Warranty
Interface products are warranted for 15 years against excessive surface wear, edge ravel, backing separation, shrinking, stretching and static electricty even under castor chair conditions.

Local Manufacturing
We combine local responsiveness with a global experience. Being part of the same communities as our customers, we foster collaborative, committed, and productive relationships. Our carpet tiles are manufactured in Australia and China, contributing to local economies and the environment.

All Interface manufacturing facilities in the Asia Pacific region maintain registration to ISO 9001 Quality Management Systems and ISO 14001 Environmental Management Systems.

Third Party Certifications

Environmental Product Declaration (EPD)
The Environmental Product Declaration (EPD) is a third party verified environmental certification classified as Type III that quantifies and verifies the lifecycle impacts of products and goods according to the International Standards Organization (ISO) 14025, 14040, 14044 and EN 15804. EPDs help customers that are environmentally driven to evaluate the performance of a product and to make the best decision when choosing a product. Interface EPDs can be found on interface.com.

Global GreenTag GreenRate - Level A
Global GreenTag's GreenRate certification is a product rating system recognised by the Green Building Council of Australia and Green Building Council of New Zealand. Its assessment scheme aligns to the Green Star® Responsible Products program. All Interface products are certified "Level A".

Best Practice Guidelines for PVC
Our product proudly holds the Best Environmental Practice (BEP) PVC certification, a recognition of compliance with stringent environmental and social criteria in PVC manufacturing. This certification is a key contributor to Green Star certification, aligning with the GBCA's Responsible Products Framework. Our commitment to BEP guidelines demonstrates our dedication to environmental responsibility and product excellence.

Singapore Green Building Product (SGBP)
The SGBP certification is designed to evaluate and certify building products that meet specific sustainability and environmental performance criteria. The certification scheme helps building professionals identify products that are sustainable and more carbon efficient. Interface carpet tile products are certified "Leader" and LVT products are at "Excellent" Level.

NSF Certification
NSF International develops public health standards and certification programs that help protect the world's food, water, consumer products and environment. Interface carpet tile products are certified "Gold".

CRI Green Label Plus
The Carpet and Rug Insitute (CRI) Green Label Plus sets higher standards for indoor air quality and ensures that customers are purchasing the very lowest emitting products on the market. Interface Carpet Tiles and TacTiles have fulfilled the requirements for this certification.

Do more on interface.com

- Browse products, save and share favourites
- See images of products in a variety of room scenes
- Browse floor designs, change colours, upload your own image, download and share
- Get full specifications, sustainability certifications and more
- Sign up to get the latest information on Interface products and news

Our EPDs and certifications contribute credits towards Green Building Council's Green Star® Responsible Products program..

Green Star is the Green Building Council of Australia's sustainability rating system for the built environment. It is used to rate new and existing buildings, new fit-outs, and new precinct developments. The Green Building Council of Australia recognises Responsible Products that may contribute to a Green Star rating through its Responsible Credits.

We have tried our very best to accurately represent product colours. However, due to the nature of printed materials, colour of actual products may vary slightly. Please request a sample to see actual product colour.

Production specifications are subject to normal manufacturing tolerances and may be changed without notice. The visibility of joints may vary based on colour and pattern. Slight variation in colour among different production lots are normal and should be considered in the overall installation plan. Products covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for particular purpose, are hereby disclaimed. Contact your representative for written warranty information.

Europe, Middle East & Africa

AE	+971 44508175
AT	+43 1 8102839
BA	+387 33 522 534
BE	+32 2 475 27 27
BG	+359 2 808 303
BY	+375 17 226 75 14
CH	+41 44 913 68 00
CZ	+42 0 233 087 111
DE	+49 2151 3718 0
DK	+45 33 79 70 55
EE	+372 6518 313
ES	+34 932 418 750
EG	+(202) 3760 7818
FR	+33 1 58 10 20 20
GR	+30 211 2120820
HR	+385 14 62 30 63
HU	+36 1 349 6545
IE	+353 1 679 8466
IL	+972 97403034
IT	+39 02 890 93678
KZ	+7 701 391 88 13
LT	+370 37 337332
LV	+371 672 18 744
NL	+31 33 277 5555
ME	+381 11 414 92 00
MK	+389 2 323 01 89
NO	+47 23 12 01 70
PL	+48 22 862 48 40
PT	+351 217 122 740
RO	+40 21 317 12 40/42/43/44
RS	+381 11 414 92 00
SA	+966 554622263
SE	+468 241 230
SK	+421 911 104 073
SI	+386 8 205 4007+
TR	**+90 212 274 44 22**
UA	+38(044)238 27 67
UK	+44 (0)800 3134465
ZA	+27 11 608 4270

www.interface.com