



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see

www.interface.com/disclaimer.

Product norament 926 arago **Colour** Tranquil **Collection** norament **Format** Tile

Surface Relief Structure **Product Options** Standard **Thickness** 3.5mm

Product Specifications

Article Number	3118
Format	Tile
Size	1004 mm x 502 mm
Surface	Relief Structure

CE Conformity

CE Conformity (EN 14041)	Manufacturer: nora systems GmbH, D-69469 Weinheim
DoP-No. (EN 14041)	0021
UK DoP-No. (EN 14041)	0021
Thermal conductivity (EN 10456)	Fulfilled ($\lambda = 0.17 \text{ W/(m·K)}$)
Dynamic Coefficient of Friction (EN 13893)	Fulfilled (DS)
Reaction to fire (EN 13501-1)	Cfl-s1 (Not bonded)

Performance Specifications

Reaction to fire (EN 13501-1)	Cfl-s1 (Not bonded) Bfl-s1 (Bonded on mineral subfloor)
Thickness (EN ISO 24346)	(Mean value $\pm 0.15 \text{ mm}$) 3.5 mm
Dimensional stability (EN ISO 23999)	($\pm 0.4 \%$) $\pm 0.2 \%$
Cigarette-burn resistance (EN 1399)	Fulfilled (Procedure A (stubbed out) level ≥ 4 , Procedure B (burning) level ≥ 3)
Flexibility (EN ISO 24344, procedure A)	Fulfilled (Mandrel diameter 20 mm, no fissuring)
Hardness (ISO 48-4)	82 Shore A ($\geq 75 \text{ Shore A}$)
Residual indentation (EN ISO 24343)	(Mean value $\leq 0.20 \text{ mm}$ at thickness $\geq 3.0 \text{ mm}$) 0.12 mm
Abrasion resistance at 5 N load (ISO 4649, procedure A)	($\leq 250 \text{ mm}^3$) 115 mm ³
Colour fastness to artificial light (ISO 105-B02, procedure 3, test conditions 6.1 a))	Fulfilled Grey scale $\geq$ level 3 acc. to ISO 105-A02 (At least level 6 on the blue scale; $\geq$ level 3 on the grey scale)
Classification (EN ISO 10874)	34/43 (Commercial/Industrial)
Toxicity of fire gases (DIN 53436)	Carbonisation gases are non-toxic
Anti-slip properties (DIN EN 16165)	R10 (According to DGUV 108-003) A,B
Improvement in footfall sound absorption (ISO 10140-3)	10 dB
Effect of chemicals (EN ISO 26987)	Resistant depending on concentration and time of exposure. In case of increased impact of oils, greases, acids, alkalis and other aggressive chemicals please contact us.
Electrical insulation properties (EN 1081 R1)	$> 10^9 \text{ Ohm}$
Electrical propensity when walked upon (EN 1815)	Antistatic, charging in case of rubber soles $< 2 \text{ kV}$
Effect of a castor chair (EN ISO 4918)	Suitable if castor wheels, type W, according to EN 12529 are used
Underfloor heating (EN 1264-2)	Suitable, max. 35 °C

Health + Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	Health Product Declaration
Indoor Air Quality & Environmental Certifications	Etiquetage A+ Byggarubedömningen Austrian eco-label Blue Angel Cradle to Cradle Silver DGNB Navigator eco-bau Global Green Tag Greenguard Gold Indoor Air Comfort Gold M1 PEFC Singapore Greenbuilding
Environmental Certifications	Cradle to Cradle Silver
Embodied Carbon (Cradle to Gate)	14.1 kg CO ₂ eq./m ²

Technical Information

Installation	Installation recommendations
Maintenance	Cleaning recommendations
NCS-Codes	norament 926 Standard Floorcoverings
Warranty	End User Product Warranty
Manufacturing Location	ISO 9001, 14001 & 50001 Certified Facilities in Germany

Accessories

nora Accessories	Download PDF
------------------	------------------------------

Downloads

nora Viewbook	Download Viewbook
nora Lookbook	Download Lookbook
nora Product Catalogue	Download Product Catalogue

Certifications

